

Network Working Group
Request for Comments: 2697
Category: Informational

J. Heinanen
Telia Finland
R. Guerin
University of Pennsylvania
September 1999

A Single Rate Three Color Marker

Status of this Memo

This memo provides information for the Internet community. It does not specify an Internet standard of any kind. Distribution of this memo is unlimited.

Copyright Notice

Copyright (C) The Internet Society (1999). All Rights Reserved.

Abstract

This document defines a Single Rate Three Color Marker (srTCM), which can be used as component in a Diffserv traffic conditioner [RFC2475, RFC2474]. The srTCM meters a traffic stream and marks its packets according to three traffic parameters, Committed Information Rate (CIR), Committed Burst Size (CBS), and Excess Burst Size (EBS), to be either green, yellow, or red. A packet is marked green if it doesn't exceed the CBS, yellow if it does exceed the CBS, but not the EBS, and red otherwise.

1. Introduction

The Single Rate Three Color Marker (srTCM) meters an IP packet stream and marks its packets either green, yellow, or red. Marking is based on a Committed Information Rate (CIR) and two associated burst sizes, a Committed Burst Size (CBS) and an Excess Burst Size (EBS). A packet is marked green if it doesn't exceed the CBS, yellow if it does exceed the CBS, but not the EBS, and red otherwise. The srTCM is useful, for example, for ingress policing of a service, where only the length, not the peak rate, of the burst determines service eligibility.

3. Metering

The behavior of the Meter is specified in terms of its mode and two token buckets, C and E, which both share the common rate CIR. The maximum size of the token bucket C is CBS and the maximum size of the token bucket E is EBS.

The token buckets C and E are initially (at time 0) full, i.e., the token count $T_c(0) = CBS$ and the token count $T_e(0) = EBS$. Thereafter, the token counts T_c and T_e are updated CIR times per second as follows:

- o If T_c is less than CBS, T_c is incremented by one, else
- o if T_e is less than EBS, T_e is incremented by one, else
- o neither T_c nor T_e is incremented.

When a packet of size B bytes arrives at time t, the following happens if the srTCM is configured to operate in the Color-Blind mode:

- o If $T_c(t) - B \geq 0$, the packet is green and T_c is decremented by B down to the minimum value of 0, else
- o if $T_e(t) - B \geq 0$, the packets is yellow and T_e is decremented by B down to the minimum value of 0, else
- o the packet is red and neither T_c nor T_e is decremented.

When a packet of size B bytes arrives at time t, the following happens if the srTCM is configured to operate in the Color-Aware mode:

- o If the packet has been precolored as green and $T_c(t) - B \geq 0$, the packet is green and T_c is decremented by B down to the minimum value of 0, else
- o If the packet has been precolored as green or yellow and if $T_e(t) - B \geq 0$, the packets is yellow and T_e is decremented by B down to the minimum value of 0, else
- o the packet is red and neither T_c nor T_e is decremented.

Note that according to the above rules, marking of a packet with a given color requires that there be enough tokens of that color to accommodate the entire packet. Other marking policies are clearly possible. The above policy was chosen in order guarantee a

deterministic behavior where the volume of green packets is never smaller than what has been determined by the CIR and CBS, i.e., tokens of a given color are always spent on packets of that color.

The actual implementation of a Meter doesn't need to be modeled according to the above formal specification.

4. Marking

The Marker reflects the metering result by setting the DS field of the packet to a particular codepoint. In case of the AF PHB [RFC2597], the color can be coded as the drop precedence of the packet.

5. Service Example

The srTCM can be used to mark a packet stream in a service, where different, decreasing levels of assurances (either absolute or relative) are given to packets which are green, yellow, or red. For example, a service may discard all red packets, because they exceeded both the committed and excess burst sizes, forward yellow packets as best effort, and forward green packets with a low drop probability.

6. Security Considerations

The srTCM has no known security concerns.

7. References

- [RFC2698] Heinanen, J. and R. Guerin, "A Two Rate Three Color Marker", RFC 2698, September 1999.
- [RFC2597] Heinanen, J., Baker, F., Weiss, W. and J. Wroclawski, "Assured Forwarding PHB Group", RFC 2597, June 1999.
- [RFC2474] Nichols, K., Blake, S., Baker, F. and D. Black, "Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers", RFC 2474, December 1998.
- [RFC2475] Blake, S., Black, D., Carlson, M., Davies, E., Wang, Z. and W. Weiss, "An Architecture for Differentiated Services", RFC 2475, December 1998.

8. Authors' Addresses

Juha Heinanen
Telia Finland, Inc.
Myyrmaentie 2
01600 Vantaa, Finland

EMail: jh@telia.fi

Roch Guerin
University of Pennsylvania
Department of Electrical Engineering, Rm 376 GRW
200 South 33rd Street
Philadelphia, PA 19104

EMail: guerin@ee.upenn.edu

9. Full Copyright Statement

Copyright (C) The Internet Society (1999). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.